

MOUNTAIN OFF ROAD ENTERPRISES LLC. P O BOX 690 DELTA, COLORADO 81416 970-625-0500

E-MAIL: info@mountainoffroad.com


www.mountainoffroad.com

INSTALLATION INSTRUCTIONS FOR: SB9037TJ

This steering brace fits 1997-2000 Jeep® TJ Wrangler vehicles with power steering. It is designed to bolt on, no drilling, grinding or welding. It bolts to the passenger side frame rail bottom hole (7/8" dia.) and clamps to the steering box housing just above the sector shaft pitman arm.

- **1.** The brace has a "flattened" end with a hole punched in it. That end goes in-between the two clamp halves at the steering box end.
- **2.** Install the clamp on the steering box housing just above the pitman arm. The proper assemble sequence is: 7/16" bolt with one flat washer under head, clamp half, steering brace, clamp half, flat washer, crimp-Loc nut.
- **3.** Insert the 7/8" x 2-1/2" long sleeve into the existing hole in the frame being careful not to loose it in the frame. Place the brace up to the passenger side frame rail. Place the flat washer under the head of the 5/8" x 4" bolt and insert it from the outside of the frame through the sleeve and through the welded end of the brace.
- **4.** Install the 5/8" lock nut on the bolt and tighten it to 80 lbs. ft. torque. Tighten the 7/16" bolts/nuts on the clamp end to 40 lbs. ft. torque.





TERMS-POLICIES:

DAMAGE CLAIMS: All orders are carefully packed, however, mishandling by the carrier can result in damage. The carrier has the responsibility for the shipment from the time it leaves our warehouse until it is delivered to you. All claims for lost or damaged goods should be reported to the carrier, not to M.O.R.E.™ LLC.

RETURNS: No returns will be accepted without prior permission from M.O.R.E.™ LLC. After you receive a Return Goods Authorization (RGA) number, merchandise must be returned prepaid and insured. A claim must be made with in 30 days from receipt of merchandise. The original invoice or a copy with the RGA number written on must accompany all returns. A 20% restocking fee will be charged on all parts returned for credit or refund unless merchandise is proven to be defective or was shipped wrong by M.O.R.E.™ LLC. No merchandise will be issued credit or refund if it has been installed, modified, used in any way or is in unsalable condition.

WARRANTY: All merchandise is warranted to be free from defects in materials and workmanship prior to installation. Any alteration or improper use will void this warranty. Because all parts we sell are intended for use in heavy-duty applications it is not possible to warrantee or guarantee the performance of any items. **M.O.R.E.™ LLC**. products and the products manufactured by others, which we sell may be subject to an infinite variety of conditions due to the manner in which they are used, serviced and/or installed. Purchasers and users of such products rely upon their own judgment as to the suitable use selection, service and installation of such products.

PRODUCT DISCLAIMER: Modification of your vehicle to enhance performance with parts sold by M.O.R.E.™ LLC. may create a dangerous condition which could cause serious bodily injury, and the buyer hereby expressly assumes all risks associated with any such modifications. All parts sold by M.O.R.E.™ LLC. and for racing or off road use only. Mountain Off Road Enterprises LLC. will not accept responsibility for personal injury or property damage arising from the failure of any parts manufactured or sold by M.O.R.E.™ LLC.

Specifications are subject to change without notice.

 $\textbf{Jeep} \$, \textbf{AMC} \$, \textbf{CJ} \$, \textbf{YJ} \$, \textbf{Wrangler} \$, \text{ are registered trademarks of DaimlerChrysler} \;.$

M.0.R.E™, BombProof™, S.R.S.™, SlipLoc™, DoubleJointed™, RockProof™, are trademarks used by Mountain Off Road Enterprises, LLC. The M.O.R.E.™ logo and these instructions are copyright©, 1999-2008.