

REDROCK^{4X4}

Contents:

- (1) Driver Side Front Seat Cover
- (1) Passenger Side Front Seat Cover
- (2) Front Headrest Covers
- (1) Driver Side Rear Seat Cover
- (1) Passenger Side Rear Seat Cover
- (2) Rear Headrest Covers

Seat Covers

(13-18 JK 4-Door)

(18+ JL 4-Door w/o Rear Armrest)

(18+ JL 4-Door w/ Rear Armrest)



Step 1\\ Front Seats

Begin by removing the headrest on each side, and sliding over the new headrest covers. Secure the cover to the headrest by velcroing them in place.



Step 2\\ Front Seats

With the headrest still removed, pull over the upper seat cover portion and secure by tucking the velcro sleeve in-between the upper and lower part of the seat to the back to velcro in place.



Step 3\\ Front Seats

Once the upper portion of the seat cover is installed, tuck the seat cover under the tabs for the headrest guides.



Step 4\\ Front Seats

Install the lower portion of the seat cover to the seat. Tuck the two buckles through the upper and lower seat joint. Route the straps under the seat from front to back. Tuck the seat cover around the seat lever.



Step 5\\ Front Seats

Connect the (2) front to back and (1) side to side clips to secure the seat cover to the lower portion of the seat. Then pull tight on the strap to ensure the seat cover is tight to the seat.



Step 6\\ Front Seats

Installation for the front is now complete.



Step 7\\ Rear Seats

Begin by unzipping the back of the upper rear passenger/middle seat cover and slide it over the headrest and down the seat. Do the same for the driver side. Then zipper the middle section closed, and slide the flap in-between the headrest and seat. Velcro to secure. Then tuck the velcro flap in-between the upper and lower seat section, and velcro to secure. *Note: The rear headrest do not come out, the covers will slide over top of them.



Step 8\\ Rear Seats

Slide on the (2) rear headrest covers. These just slide on, and do not velcro.




Step 9\\ Rear Seats

Insert the lower passenger and driver side seat covers. Tuck the buckles in-between the upper and lower seat section.



Step 10\\ Rear Seats

From the back of the rear seats, pull the buckles from the lower seat cover and tuck under the seat.



Step 11\\ Rear Seats

From underneath the seat, connect the front to back straps to the buckles. Pull tight on the strap to secure the cover to the lower seats.



Step 12\\ Rear Seats

Installation for the rear is now complete.