



LED FOG LIGHTS WITH RGB HALO

(2007-2018 WRANGLER JK)

INSTALLATION INSTRUCTIONS

CONTENTS

- (2) Fog Lights
- (2) Fog Light Connectors
- (2) Splice Harnesses
- (1) RGB Harness

TOOLS REQUIRED

- Socket Wrench
- 8mm Socket
- Wire Strippers

STEP 1



Access the connectors on the rear of the fog lights from the wheel well. Push in the connector tab and unplug the connector.

Note: Light connector will be different between 07-09 and 10-18.

STEP 2



Remove the (4) Phillips screws holding the fog light into the bumper.

Note: Factory hardware will be reused.

STEP 3



Install the new LED fog lights reusing the original hardware. Splice the supplied splice harness into each factory fog light harness. Connect the RGB harness to each fog light. Splice the RGB harness to the vehicle following the diagram below.

RGB Harness	-	Vehicle
Red	-	Key On Power Source
Black	-	Good Chassis Ground

STEP 4



Scan the QR code on the RGB harness. Download the app, then turn Bluetooth on. With the lights powered on, open the app and the lights will auto detect the device (Confirm in the "Group Manage" portion of the app). Press the "Power" icon at the top of the screen to change light options.

Installation is now complete.