



---

# LED HEADLIGHTS WITH RGB BACKLIGHT

(1997-2018 WRANGLER TJ & JK)

---

## INSTALLATION INSTRUCTIONS

### CONTENTS

---

- (1) Pair of LED Headlights
- (2) Anti-Flicker Harnesses
- (2) Headlight Adapters
- (1) RGB Wiring Harness
- (4) Single Wire Harnesses

### TOOLS REQUIRED

---

- Panel Removal Tool
- T15 Torx Screwdriver



**STEP 1**

Open the hood. Remove (6) plastic push clips using a panel removal tool.



**STEP 2**

Firmly pull the lower portion of the grille away from the vehicle to dislodge the lower clips from the grille. Unplug the turn signal harnesses from the turn signal housings.



## STEP 3

Remove (4) T15 Torx screws from the headlight assembly. Unplug the connector from the light by sliding back the red slider, then pushing down the plastic tab. Remove the light from the vehicle.



## STEP 4

Route the provided RGB harness across the engine bay to both headlight buckets. Connect the headlight adapter, anti-flicker harness, RGB harness to the headlight assembly. Connect the single wire harnesses to the remaining (2) wires attached to the headlight assembly. Install the new headlight into the vehicle reusing the original trim ring and hardware.



---

## STEP 5

Wire the (2) attached headlight wires to the vehicle following the provided diagram. Reassemble vehicle following steps 1-3 in reverse order.

<u>Vehicle Harness</u>	-	<u>Headlight Harness</u>
Turn Signal	-	Blue
Parking Light Power	-	Green

Installation is now complete.