



# REAR FLOOR MOUNTED CUP HOLDER

(2018-2023+ WRANGLER JL - 4 DOOR)  
(2020-2023+ GLADIATOR JT)

---

## INSTALLATION INSTRUCTIONS

### CONTENTS

---

(1) Cup Holder

### TOOLS REQUIRED

---

T-20 Torx Screwdriver  
Flathead Screwdriver  
Plastic Pry Tool  
10mm Socket  
Ratchet

SKU # J152407



## STEP 1

Engage the vehicle emergency brake. Lift the center console lid. Remove (2) T-20 Torx screws behind the backside of the lid.



## STEP 2

Slide both front seats all the way forward. Using a flathead screwdriver, pry the bolt covers from each side of the center console. Remove the (1) 10mm bolt from each side of the center console.

## STEP 3



Using a plastic pry tool, pry the upper portion of the center console away from the center console assembly. Unplug the various electrical connectors. Set panel aside.

## STEP 4



Remove (2) T-20 Torx screws from the top of the storage bin.





## STEP 5

Lift the center console assembly as much as possible. Reach under the storage tray and remove (2) T-20 Torx screws. Reference the new cup holder to approximate the screw locations.



## STEP 6

With the storage tray removed, remove the (2) metal clips from the storage tray using a flathead screwdriver, then transfer the clips to the new cup holder.



---

## STEP 7

Re-assemble vehicle following steps 1-6 in reverse order.

Note: Be sure the cup holder is not resting on the floor mat during re-assembly.



---

## STEP 8

Installation is now complete.