

LED FENDER VENT COURTESY LIGHT

(2018-2021 WRANGLER JL) (2020-2021 GLADIATOR JT)

INSTALLATION INSTRUCTIONS

CONTENTS

- (1) LH Fender Vent Light
- (1) RH Fender Vent Light
- (4) Adhesion Promoter Pads
- (8) Wire Holders
- (8) Wire Holder Adhesive Pads
- (1) Wiring Harness

TOOLS REQUIRED

Plastic Pry Tool 10mm Wrench





Clean the vehicle fender using the provided adhesion promoter pads along the indicated area.

Repeat this procedure to the opposite side fender light.



Using a plastic pry tool, pry back on the vehicle accent trim enough to insert the vent light wiring to the engine bay.

Repeat this procedure to the opposite side fender light.





STEP 3

Familiarize the fitment of the fender light. Peel the double sided tape backing from the fender light, then align the fender light to the vehicle. Repeat this procedure to the opposite side fender light.

Note: Ensure the wiring harness is inside the cutout in the fender light to ensure a flush fit to the vehicle.



STEP 4

Connect both fender lights to the wiring harness. Route the wiring harness leads into the interior of the vehicle through a suitable driver side firewall grommet. Splice into the footwell light following the diagram below.

<u>Vent Light Wiring Harness</u> - <u>Vehicle Wiring Harness</u>

Red - <u>Vehicle Wiring Harness</u>
Footwell Light + (Yellow/Violet)

Black - Ground/Negative Battery Terminal (Black)





Neatly route the wiring harness throughout the vehicle.

Installation is now complete.

STEP 5