



LED SIDE MARKER LIGHTS

(2018+ WRANGLER JL)
(2020+ GLADIATOR JT)

INSTALLATION INSTRUCTIONS

CONTENTS

- (1) LH Fender Light
- (1) RH Fender Light
- (6) Scotchlok Connectors
- (2) Alcohol Prep Pads

TOOLS REQUIRED

- Plastic Panel Removal Tool
- Wire Strippers
- Isopropyl Alcohol
- Microfiber Cloth

STEP 1



Using a plastic pry tool, gently pry around the plastic fender trim to dislodge the trim from the fender. Remove fender trim from vehicle. Clean the fender area with isopropyl alcohol and a microfiber cloth.

STEP 2



Peel the double sided tape backing from the fender vent light. Route the attached wiring into the engine bay where accessible for wiring. Align the top of the side marker light into the fender, then align the bottom into the fender. Ensure the light clips into place.



STEP 3 (WIRING)

Route the wiring towards the fender mounted turn signal/parking light. Wire the LED marker light into vehicle following the diagram below.

<u>LED Marker Light</u>	-	<u>Vehicle Wiring</u>
Red	-	White/Red Stripe (Parking Light)
Green	-	White/Brown Stripe (Turn Signal)
Black	-	Ground



STEP 4

Repeat steps 1-3 to the opposite side.

Installation is now complete.