



LIMB RISERS

(1997-2006 WRANGLER TJ)

INSTALLATION INSTRUCTIONS

CONTENTS

- (1) LH Windshield Frame Mount
- (1) RH Windshield Frame Mount
- (2) Hood Latch Mounts
- (2) Limb Riser Cables
- (6) Rivets
- (2) Tapered Allen Bolts
- (2) Flat Washers
- (2) Lock Nuts

TOOLS REQUIRED

- 10mm, 13mm Sockets
- Ratchet
- Rivet Gun
- Marker
- Drill



STEP 1

Open the vehicle hood, and remove (2) 10mm nuts from the hood catch. Remove the hood catch from the vehicle.



STEP 2

Place (1) hood latch mounting bracket in between the vehicle hood and the original hood catch. Secure the assembly to the vehicle using the original (2) 10mm nuts.

STEP 3

Temporarily attach the limb riser cable to the hood mounted bracket and the windshield frame bracket. Extend the cable and test fit the limb riser to the windshield frame to determine the appropriate bracket mounting location.

Note: Ensure the adjustment collar is properly adjusted to allow adding tension when the cable is mounted.

STEP 4

Using the windshield frame mounting bracket as a template, mark the (3) holes onto the windshield frame using a marker, and drill into the windshield frame. Once drilled, align the bracket and rivet the bracket to the vehicle.



STEP 5

Connect the limb riser cable to each mounting bracket using the provided hardware. Tighten the middle collar to the appropriate tension. Repeat steps 1-5 to the opposite side of the vehicle.

Installation is now complete.