



REAR WINDOW MOUNTED LED LIGHT BARS

(2018+ WRANGLER JL)

INSTALLATION INSTRUCTIONS

CONTENTS

- (2) Mounting Brackets
- (1) Switch Harness
- (2) LED Lights
- (4) M6x1.00 x 15mm Allen Bolts
- (4) M6 Lock Washers
- (4) M6 Flat Washers
- (1) Allen Key

TOOLS REQUIRED

- Panel Removal Tool
- 10mm Socket
- Ratchet
- Cable Ties
- Isopropyl Alcohol
- Microfiber Cloth

STEP 1



Using a panel removal tool, pry the bottom of the rear glass hinge cover to release the retaining clips.

STEP 2




Hinge the plastic cover upwards, and push the cover inwards to release the retaining hooks. Set the cover aside for reinstallation later.



STEP 3

Remove (2) 10mm bolts from the hard top hinge.

Note: Only remove the hinge bolts from one side of the vehicle at a time.



STEP 4

Place the mounting bracket in between the hard top and the rear window hinge. Secure the bracket into place using the (2) original 10mm bolts.

Note: Do not install the hinge cover until final adjustments are made.



STEP 5

Install the LED to the mounting bracket using (2) M6x1.00 x 15mm Allen bolts, (2) M6 lock washers, and (2) M6 flat washers.



STEP 6

Install the original hinge cover once aiming adjustments are completed. Repeat steps 1-5 to the opposite side of the vehicle for the remaining mounting bracket.

See the following page for wiring instructions.



STEP 7 (WIRING)

LED Wiring: Connect the LED lights to the provided wiring harness. Route the wiring harness down the passenger side of the vehicle frame towards the battery. Route the switch through a suitable firewall grommet. Clean the vehicle dashboard with isopropyl alcohol and a microfiber cloth, and adhere the switch to the vehicle dashboard. Connect the terminals to the battery using the following diagram

<u>Vehicle Battery</u>	-	<u>LED Wiring Harness</u>
Positive Terminal (+)	-	Red (+)
Negative Terminal (-)	-	Black (-)