

LED TAIL LIGHTS

(2007-2018 WRANGLER JK)

INSTALLATION INSTRUCTIONS

CONTENTS

- (1) LH Tail Light
- (1) RH Tail Light
- (2) Resistor Brackets
- (4) Phillips Head Bolts
- (4) Lock Nuts
- (4) Phillips Head Screws
- (4) Vampire Clips

TOOLS REQUIRED

- Phillips Screwdriver
- Isopropyl Alcohol
- Microfiber Cloth
- Pliers

STEP 1



Remove (2) Phillips screws from the tail light assembly.

STEP 2



Unplug the wiring harness from the back of the tail light. Remove the tail light from the vehicle.

STEP 3



Install the resistor bracket to the resistor using (2) Phillips bolts and (2) lock nuts, tighten until secure.

STEP 4



Clean the area around the tail light cutout in the body using isopropyl alcohol and a microfiber cloth. Allow the area to fully dry, peel the red tape backing from the tail light rear bracket. Place the bracket to the vehicle, aligning the (2) screw holes with the original tail light mounting holes. Secure the bracket into place using the (2) original tail light mounting Phillips screws.



STEP 5

Secure the resistor & bracket to the inside of the vehicle body using (2) vampire clips. Plug in the tail light to the vehicle wiring harness. Clip the tail light assembly into the rear bracket. Once properly fitted, secure the tail light to the bracket using the (2) provided Phillips screws.



STEP 6

Repeat steps 1-6 to the remaining tail light assembly on the opposite side of the vehicle.

Installation is now complete.