

FENDER VENT LED LIGHTS

(2018-2023+ WRANGLER JL)

(2020-2023+ GLADIATOR JT)

INSTALLATION INSTRUCTIONS

CONTENTS

- (1) LH Fender Light
- (1) RH Fender Light
- (6) Zip Ties
- (6) Scotchlok Connectors

TOOLS REQUIRED

- Plastic Panel Removal Tool
- Wire Strippers
- Isopropyl Alcohol
- Microfiber Cloth

STEP 1



Using a plastic pry tool, gently pry around the plastic fender trim to dislodge the trim from the fender. Remove fender trim from vehicle. Clean the fender area with isopropyl alcohol and a microfiber cloth.

STEP 2



Peel the double sided tape backing from the fender vent light. Route the attached wiring into the engine bay where accessible for wiring. Align the top of the fender vent light into the fender, then align the bottom into the fender. Ensure the light clips into place.



**STEP 3
(WIRING)**

Route the wiring towards the fender mounted turn signal/parking light. Wire the fender light into vehicle following the diagram below.

Fender Light	-	Vehicle Wiring
Red	-	White/Red Stripe (Parking Light)
Yellow	-	White/Yellow Stripe (Turn Signal)
Black	-	Ground



STEP 4

Repeat steps 1-3 to the opposite side.

Installation is now complete.