



HOOD GUARD WITH LED LIGHTING

(2018-2024+ WRANGLER JL)
(2020-2024+ GLADIATOR JT)

INSTALLATION INSTRUCTIONS

CONTENTS

- (1) Hood Guard
- (1) Wiring Harness
- (12) Wire Retainers
- (2) Scotchlok Connectors
- (2) Adhesion Promoter Prep Pads
- (2) Alcohol Prep Pads
- (1) Roll of Double Sided Tape

TOOLS REQUIRED

- Exterior Detailer
- Microfiber Cloth

STEP 1



Plug the wiring harness into the LED lights. Adhere the included (4) wiring retainers to the inside of the hood guard to retain the wiring harness away from the spoiler mounting points.

STEP 2



Clean the outer boarder of the hood guard using (1) alcohol prep pad, followed with (1) adhesion promoter prep pad. Then, install the included double sided tape to the boarder of the hood guard. Firmly press the tape into the spoiler to encourage adhesion.



STEP 3

Clean the vehicle hood using exterior detailer and a microfiber cloth. Test fit the hood guard to the vehicle to familiarize fitment. Once familiar, clean the hood guard mounting area of the hood using (1) alcohol prep pad, followed by (1) adhesion promoter prep pad.

Note: It is recommended to allow the guard to rest in the sun prior to installation to encourage material manipulation.



STEP 4

Peel the red tape backing from the hood guard, and route the harness towards the side edge of the guard. Align and firmly press the hood guard into the vehicle hood to ensure proper adhesion.



STEP 5

Route the wiring harness towards the vehicle parking lamps. Using the (2) scotchlok connectors, splice the hood guard lights into the vehicle parking lamps. Route the harness using (8) retainers.

Hood Guard Harness

Red	-	Parking Lamp 12V +
Black	-	Chassis Ground

Installation is now complete.