



9400 Installation Instructions

Product Overview:

The Eagle Lights plug and play LED tail lights for JEEP Jk models! No additional adapters or wiring needed.

Typical Installation

Normal installation requires only a few tools, takes less than 45 minutes and requires no wiring on most installations.

Installation Warning

If you feel uncomfortable installing this product, we recommend having a professional complete the installation. Eagle Lights LLC is not liable for any damage to the product or vehicle due to an improper installation.

If you have questions about the installation, please feel free to call us at 1-800-921-3162 or email us at Support@EagleLights.com.

Installation:

Below are steps for typical installations on most JK models. Steps may be different depending on the model and year of Jeep Jk. Please ensure you have read through the instructions and understand them clearly before attempting the installation.

 WARNING! 
<ul style="list-style-type: none">• To prevent possible electrical shock, disconnect the negative battery terminal before installing this product.

- Detach your existing tail light by unscrewing the two inside screws. Keep these screws. Pull the tail light out toward you to remove it from the housing.
- Unplug the connector from the back of the existing tail light
- Plug in the new tail light connector, then tuck the wiring back into the vehicle's cavity.
- Fasten the resistor to the Jeep. Keep the resistors out of the way from wiring. The resistor can get hot and needs to be kept away from other wiring.
- Starting with the bottom inside screw, attach the new tail light using the vehicle's existing screws
- Repeat steps 1-9 on the other tail light.
- Test light functions