



FENDER FLARE EXTENSIONS

(2007-2018 WRANGLER JK)

INSTALLATION INSTRUCTIONS

CONTENTS

- (1) LH Front Flare Extension
- (1) RH Front Flare Extension
- (1) LH Rear Flare Extension
- (1) RH Rear Flare Extension
- (18) Plastic Rivets
- (6) Self Tapping Screws

TOOLS REQUIRED

- Plastic Rivet Install Tool
- Phillips Screwdriver/Drill Bit
- Side Cutters

SKU # J237927

STEP 1 [FRONT]



Along the inside edge of the fender flare, locate the fender liner plastic rivets. Hold the appropriate front flare extension to the fender flare, and identify the rivets that will need to be removed from the fender flare, as well as the (2) open holes for self tapping screws.

Once all mounting locations are identified, remove the OE plastic rivets from the fender flare.

STEP 2 [FRONT]



With a helper, hold the flare extension to the vehicle, and begin to install the provided (4) plastic rivets and (2) self tapping screws into the fender flare. Some manipulation will be required to ensure all fastener holes align.

Repeat steps 1-2 to install the remaining front fender flare extension.

STEP 3

Along the inside edge of the fender flare, locate the fender liner plastic rivets. Hold the appropriate rear flare extension to the fender flare, and identify the rivets that will need to be removed from the fender flare.

Once all mounting locations are identified, remove the OE plastic rivets from the fender flare.

STEP 4

With a helper, hold the flare extension to the vehicle, and begin to install the provided (4) plastic rivets into the fender flare. Some manipulation will be required to ensure all fastener holes align.

Repeat steps 3-4 to install the remaining rear fender flare extension.

Installation is now complete.