

JL STYLE LED TAIL LIGHTS

(2007-2018 WRANGLER JK)

INSTALLATION INSTRUCTIONS

CONTENTS

- (1) LH Tail Light
- (1) LH Tail Light Bracket
- (1) RH Tail Light
- (1) RH Tail Light Bracket
- (4) Phillips Screws
- (2) Top Screw Cover
- (2) Bottom Screw Cover

TOOLS REQUIRED


- Phillips Screwdriver
- Isopropyl Alcohol
- Cotton Swab

SKU # J240904



STEP 1

Remove (2) Phillips screws from the inner-most side of the tail light.



STEP 2

Firmly pull the tail light away from the vehicle, and unplug the gray electrical connector by pressing the tab and separating the connectors.



STEP 3


If necessary, separate the tail light bracket from the tail light assembly, and unplug the side marker from the tail light harness connector.

Fit the tail light bracket to the vehicle with the vehicle harness through the bracket hole. Secure the bracket to the vehicle using the original (2) Phillips screws.



STEP 4

Plug in the tail light harness to the vehicle tail light connector. Then, connect the tail light harness to the side marker light harness attached to the bracket.



STEP 5

Fit the inner-most side of the tail light into the bracket, then press the outer side of the tail light into the bracket to engage the mounting clips.




STEP 7

Repeat Steps 1-6 for the remaining tail light assembly.

Installation is now complete.

STEP 6



Secure the tail light to the bracket using (2) Phillips screws in the ports on the outside of the tail light bracket. Tighten the screws until the tail light is secure.

Clean the screw hole port ledge using a cotton swab and isopropyl alcohol and allow to fully dry. Once dry, identify the top/bottom plastic covers. Peel the tape backing on each cover, and firmly press the cover over the tail light bracket screw part.