

CUSTOM-FIT CAR STEREO FOR JEEP WRANGLER 2018-2023 GLADIATOR 2020-2023



VISION Series INSTALLATION MANUAL

Important Notice!

Please read this installation guide carefully before disassembling your vehicle or making any wire connections Installing this product requires technical expertise, experience and specialized tools.

If you are unsure about performing the installation steps outlined in this manual, we strongly recommend having the product professionally installed by an authorized VINLAND dealer.

Contents

Before Installation	1
1. Notification	1
2. Packing List	1
Chapter 1 Maestro RR Configuration	3
Chapter 2 Inputs/Outputs	11
Chapter 3 Installation Process	11
1. Disassembly and Assembly	11
2. Cable Harness Connection	

Before Installation

1. Notification

Warning

- New system updates may be released, which may include changes made or newly added functions that are not mentioned here.
- Users can contact customer support to download the latest Installation Manual.
- The information in this manual may be insufficient. If you have any questions or problems concerning your unit that are not covered in this manual, consult customer support.

Tools you may need to prepare yourself in advance:

- Plastic pry tools
- Socket wrench (7mm or 10mm depending on your stereo)
- Screwdriver
- Electrical tape
- Scissor
- Wrench
- Screw Tray/Box
- Cable Ties

2. Packing List









Chapter 1 Maestro RR Configuration

To ensure proper operation and communication with your vehicle, please install Weblink Desktop before using the Maestro RR. It is essential for device configuration, data transfer, and remote management.

1. Download and Install Weblink Desktop Software

Go to https://www.weblinkupdater.com/weblinkdesktop/en and download the Weblink Desktop software.



2. Create or log in to your Weblink account.





3. Connect the Maestro RR module to your computer using a USB cable (in Maestro RR package) and select the "Maestro Flash

Weblink Desktop 1.3.10.0	- • ×
	En Fr Please choose one of the following projects:
A newer, quicker way to experience Weblink programming from your PC or Mac deaktop computer – without using a web-browser. To get started, connect your compatible ADS product choose a project, log in and follow the programming steptin. Install guides as well as available wring information and videos will be provided once flashing is complete.	Weblink RS Flash Remote Starter
For technical support, contact ADS Ioli-free at 1.866.427.2999 or visit our IbataTech Facebook Group.	Maestro Flash Maestro
Access my profile, advanced analytics: Profile	Log Out
IData, IDatalink, IDatastart, KLON, Maestro and Weblink are registered trademarks of Automotive Data Solutions Inc. Automotive Data Solutions Inc. 2020 Ibac. Agreement & Privacy Policy	

Maestro ".

4. Identify the Module Information

Weblink Desktop will automatically detect the connected Maestro RR module and display its information (e.g., serial number and current firmware version).

Tap "FLASH BY VEHICLE" to process.





5. Select Vehicle and Head Unit Information

Input the required details in the following order:

1 Select vehicle manufacturing year and vehicle brand





② Select model and configuration



③ Select your steering wheel



④ Select the head unit brand - VINLAND



(5) Select the specific model that matches the head unit you purchased.



6 Enter the car stereo 8-digit Serial Number which is ticketed on the back of the

head unit, find and enter it.

≡	maestro	Radio Brands Radios	
Rr	VIN-MRR / E1028F0C82 / 2019 / Jeep / Wrangler	K - 7" Screen Altermarket Radio must be Shallow Mount Does Not Retain Back Up Camera / Vinland	
Ē			
0		SELECT YOUR VINLAND RADIO MODEL	
		Select the aftermarket radio you are installing. If necessary, enter the serial number of the actual radio you are installing.	
		For assistance locating the device/serial number on radio head units, click here.	
		Radio serial number	
00		Please enter the serial number of the radio being installed. This is needed for Maestro to	
DR,		communicate with this radio. This information will not be made public.	
		642de792	
		How to find the serial number	
		V13WR182309	
		Copyright & 2025 ADS: All Rights Reserved v1.42.3 User Agreement & Privacy Policy	

Each head unit has a unique Serial Number. Please refer to the one on your device.





O Select the firmware version



6. Select the accessories you are using





7. Configuration

The system will automatically choose the recommended settings for your screen. If no changes are needed, just click CONTINUE to move on to the next step.

≡	maestro					
Rr	VIV-MR8 / E1028F0C82 / 2019 / Jeep / Wangler JL - 7 Screen Altermarker Radio must be Shallow Mount Dees Hot Retain Black Up Camera / Vinland / V13WR182209 / O10-VIV-RR V1.0					
A						
0		SELECT HUW YUU WA	ANIIU	O CONFIGURE YOUR SYST	ΕM	
		Vehicle Info		Park Assist		
		Gauges		Climate Control		
		Advanced Camera Features		Rear Seat Video Retention		
60		Secondary Vehicle Display (If equipped)		Factory Amplifier	? 🌑	
Þ.		Steering Wheel Controls		OEM Camera		
\downarrow				· · · · · · · · · · · · · · · · · · ·		
		Copyright @ 2025 ADS	All Rights Reserve	d v.1.42.31 User Agreement & Privacy Policy		CONTINUE

8. Customize Steering Wheel Control Functions

Default steering wheel button functions will be displayed in the interface.

Modify the button assignments as per user requirements, if necessary, and save the settings.





9. Review & Flash Firmware

Review the firmware version, custom settings, and vehicle/head unit info.

Click "FLASH" to update the Maestro RR module. Do not disconnect the module or USB

during the process.



10. Complete the Flashing Process

Once the firmware update is complete, you will see a "Flash Successful" message.

Download the installation guide for the module and proceed with the next steps for in-vehicle installation.



Chapter 2 Inputs/Outputs



Rear Right Audio Output
 Front Right Audio Output
 Subwoofer Output Right
 Right Channel Auxiliary Audio Input
 Coaxial Output
 Rear Camera Input
 Rear Camera Input
 Rear Left Audio Out
 Stront Left Audio Out
 Subwoofer Output Left
 Left Channel Audio Input
 Yideo Input
 Front Camera Input
 Subsoofer Output Left
 Usideo Input
 Kideo Input
 Subsoofer Output
 Subwoofer Output Left
 Usideo Input
 Subsoofer Output
 Video Input
 Subsoofer Output
 Subsoofer Output

16. USB1 Recording Storage
17. Rear Recording Camera Input Front Recording Camera Input
18. HDMI Input
19. 4G LTE Adapter Interface
20. F-M-ANT-Radio Antenna input
21. 4-in-1 Antenna-4G/WiFi/GPS
22. Car Stereo Fuse

Chapter 3 Installation Process

1. Disassembly and Assembly

No.	Operation	Image			
	Part 1 Disassembly				
1	Switch the ignition key to the "OFF" setting.	NLL ON THE			



2	Use a plastic pry tool to gently loosen and release the A/C control panel. Then disconnect the wiring harness and antenna from the back		
3	Remove the two screws at the base of radio trim.		
4	Grip the four corners of the unit frame and pull gently to remove it.		
5	Remove the four screws securing the stereo into the dash. Carefully take out the stereo and unplug all connected cables.		
Part 2 Cable Harness Connection			
Refer to the detailed wiring connection steps provided below the table.			
Part 3 Assembly			



Install the new car stereo along with its panel into the vehicle. Reinstall the A/C control panel



2. Cable Harness Connection

STEP 1

①Connect the main harness of the HRR-CH3 T-harness to car stereo Directly.

OR

②Connect the HRR-CH3 harness to the **Power Adapter**.

STEP 2

• Determine if the vehicle has a factory amplifier. Look for badges on the radio, door panels and dash that indicate the presence of an amplifier.

If the vehicle DOES NOT have a factory amplifier:

• Plug the female BLACK connector to the male BLACK connector of your HRR-CH3 T-harness.

 Plug the female WHITE connector to the male WHITE connector of your HRR-CH3 T-harness.

If the vehicle DOES have a factory amplifier:

• Plug the female BLACK connector to the male WHITE connector of your HRR-CH3 T-harness.

• Plug the female WHITE connector to the male BLACK connector of your HRR-CH3 T-harness.

• Connect the factory radio harness to the HRR-CH3 T-harness.

STEP 3

• Connect the black 2-pin connector from the extension cable to the CH3 main harness. Route the white ends to the CAN junction block in vehicle (see diagram for location). Unplug any one of the 2-pin white connectors in it. Insert the male white end from the Maestro harness into the junction block and plug the factory 2-pin connector back into the Maestro



female white 2-pin.

STEP 4

Plug the **mini USB Adapter** into vehicle, and the other end to **USB1** cable.

STEP 5

• Plug the harnesses into the car stereo.

• Plug the CH3 Radio Antenna Adapter into the car stereo's FM-ANT port, and the other end to the vehicle.

Connect the AUX Cable as follows:
 Two RCA connectors→ Plug into the car stereo's RIN and LIN ports.

Other end \rightarrow Insert the audio jack from the **Audio Cable**.

STEP 6

Plug the ADS Data Cable of the Power
Adapter to the Maestro RR module.

OR

Plug the data cable from **Main Harnes**s to the Maestro RR module.

• Plug the other end of **Audio Cable** into Maestro RR module.

• Connect all the harnesses to the Maestro RR module then test your installation.



WIRING DIAGRAM



[Connection Diagram of 2018-2023 JEEP WRANGLER JL & 2020-2023 JEEP GLADIATOR]



www.vinlandonline.com support@vinlandonline.com

