




**757-842-6497**  
**WWW.JLOSC.COM**

**J&L Oil Separator, Passenger Side**  
**(2011-2023 SRT 6.4 L HEMI Charger, Challenger, 300C, Jeep Grand Cherokee &**  
**2018-2024 Durango SRT8)**  
**#3063P**

**Installation Instructions**

**Install video available at our website [www.JLosc.com](http://www.JLosc.com) Search: 3063P and click videos.**

**Please review complete instructions prior to installing.**

Step#	
<b>1</b>	<b>Verify you have all of the following parts included in the kit:</b> (1) J&L Oil Separator w/fittings, (1) J&L Mounting Bracket, (2) Fine Thread Machine Screws, (1) 11" hose with fitting
<b>2</b>	<b>Gather all of the following tools needed for the installation:</b> 15mm socket and ratchet and Phillips screwdriver. A Pair of pliers.
<b>3</b>	Remove the factory PCV hardline from both rubber connection points. You may need to twist the rubber ends with pliers to break seal on connections. 
<b>4,5,6</b>	<b>4)</b> Install mounting J&L bracket to engine using existing 15mm bolt. <b>5)</b> Mount Separator onto J&L bracket using supplied screws. <b>6)</b> Slide elbow onto oil separator fitting



Use light oil on the fitting into rubber connector on intake manifold (near PCV cap)



7



To properly clean the filter in the Oil Separator, spray any degreaser or solvent through it and let it air dry. Clean it every 10,000 miles.

Thank you for your business. If you have any questions, please e-mail [info@JLosc.com](mailto:info@JLosc.com) or call 757-842-6497. Our hours are Monday-Friday. 8:00am – 4:30pm Eastern Time.

**J&L Oil Separator co. Lifetime Satisfaction Guarantee. We want you to be a J&L customer for life!** Your new J&L product is warranted to be free from defects in materials and workmanship for the life of the *original retail purchaser*, subject to the limitations contained in our warranty found here. [www.JLosc.com/warranty](http://www.JLosc.com/warranty)

We guarantee workmanship and even a pathway to discounted upgrades for substantially improved items.

**Return Policy:** All returns will be subject to a 10%-25% restocking fee. Please visit [www.JLosc.com](http://www.JLosc.com) for complete return policy.

**Disclaimer:** J&L Oil Separator co. makes no warranties whatsoever, expressed, or implied, oral or written to any purchasers, except the warranty above. J&L Oil Separator co. hereby specifically excludes from any implied warranty of merchantability or implied warranty of incidental, secondary, or consequential damages of any kind whatsoever. All purchasers and users of products manufactured by J&L Oil Separator co. agree to hold harmless and indemnify J&L Oil Separator co. from any and all claims arising from their use. Failure to receive notice of any or the limitations contained in this disclaimer shall not serve to extend liability to J&L Oil Separator co. for any claims arising out of use of its products.