



757-842-6497
WWW.JLOSC.COM

**J&L 3.0 Oil Separator (2003-2015 Nissan Titan 5.6L Passenger Side) #3103P
Installation Instructions**

Install video available at our website www.JLosc.com Search: 3103P and click videos

Please review complete instructions prior to installing.

Step#	
1	Verify you have all of the following parts included in the kit: (1) J&L Oil Separator, (1) J&L Mounting bracket, (2) Fine thread machine screws, (2) Hose assemblies, (1) Spacer, (1) M6 bolt
2	Gather all of the following tools needed for the installation: 10mm Socket and ratchet, Phillips screwdriver, pliers
3	Remove engine cover by removing the (2) 10mm bolts and pulling up on the cover.
4	Remove factory PCV lines on each valve cover PCV valve and rotate them both toward the front of the engine 
5	Remove bolt from upper radiator fan shroud. Use the J&L supplied spacer and J&L bolt to mount the bracket to the upper fan shroud mount. 

6	Install J&L can onto J&L Bracket using the two supplied screws, the J&L Logo should line up with the can and bracket.
7	Take single hose with T fitting in it and connect to the "O" (OSC) side of the separator and to the factory hoses from step 4. Be sure to slide factory spring clamps to fasten hoses to T fitting.
8	Take hose assembly with T fitting and 3 hoses and connect to the "C" (OSC) side of the separator to the shortest hose and connect the other two hoses to the PCV valves on each valve cover.
9	Reinstall engine cover



To properly clean the filter in the Oil Separator, spray any degreaser or solvent through it and let it air dry. Clean it every 10,000 miles.

Thank you for your business. If you have any questions, please e-mail info@JLosc.com or call 757-842-6497. Our hours are Monday-Friday. 8:00am – 4:30pm Eastern Time.

J&L Oil Separator co. Lifetime Satisfaction Guarantee. We want you to be a J&L customer for life! Your new J&L product is warranted to be free from defects in materials and workmanship for the life of the *original retail purchaser*, subject to the limitations contained in our warranty found here. www.JLosc.com/warranty

We guarantee workmanship and even a pathway to discounted upgrades for substantially improved items.

Return Policy: All returns will be subject to a 10%-25% restocking fee. Please visit www.JLosc.com for complete return policy.

Disclaimer: J&L Oil Separator co. makes no warranties whatsoever, expressed, or implied, oral or written to any purchasers, except the warranty above. J&L Oil Separator co. hereby specifically excludes from any implied warranty of merchantability or implied warranty of incidental, secondary, or consequential damages of any kind whatsoever. All purchasers and users of products manufactured by J&L Oil Separator co. agree to hold harmless and indemnify J&L Oil Separator co. from any and all claims arising from their use. Failure to receive notice of any or the limitations contained in this disclaimer shall not serve to extend liability to J&L Oil Separator co. for any claims arising out of use of its products.