

Ditch Light Bracket Kit Part Number: DTC-100

Toyota 2010-2022 4Runner 2.7L/4.0L

Installation Instructions

For technical inquiries please email us at tech@hpsperformanceproducts.com

In the email, please include the following information for faster response:

- Year / Make / Model / Engine of your vehicle.
- If it is a fitment issue, please include pictures showing the fitment problem.
- If there are missing parts, please list the part number(s) from the bill of materials on the 2nd page.
- Optional but recommended Your contact phone number and preferred call back time.

You can also give us a call via 626-747-9200 for tech support Monday-Friday, 9:00am-5:00pm Pacific Time.

Bill of Materials

Kit Number: DTC-100

| Line # | Description | Part Number | Qty |
|--------|-------------------------------|-------------|-----|
| 1 | Left Ditch Light Bracket | DTC-100-L | 1 |
| 2 | Right Ditch Light Bracket | DTC-100-R | 1 |
| 3 | M8 x 1.25mm Thread, 30mm Long | 95735A431 | 4 |
| 4 | M8 Flat Washer 16mm OD | HW-FW8S | 4 |



- Before installing any parts of this ditch light bracket kit, please read the instructions thoroughly.
- Verify the contents of this ditch light bracket kit before disassembling your vehicle.
- Report any defective or missing parts to HPS directly. The HPS dealer you purchased this product from might not have the replacement parts you need.
- Installation requires moderate mechanical skills. A qualified mechanic is highly recommended.
- For technical inquiries, please email us at tech@hpsperformanceproducts.com

PLEASE READ CAREFULLY BEFORE INSTALLATION!

Install this kit with caution! Misuse of this product can damage parts of your vehicle.

NOTE: HPS holds no responsibility for any damage that results from misuse of this product.

GETTING STARTED





2. Install the driver's side bracket by hand tightening the provided washer and M8 bolt. Angle the bracket to give clearance to the rear hood hinge bolt for removal.



3. Remove the rear bolt from the hood hinge in order to rotate the bracket to line up the rear hood hinge mounting hole and rear bracket mounting hole. Install and hand tighten the provided washer and M8 bolt.



4. Before tightening the bolts, check for clearance between the hood and the ditch light bracket. Adjust the bracket accordingly and make sure to realign the hood to its original position.



5. Repeat steps 2-4 on the passenger's side.

NOTE: There is a washer fluid hose in the way of the hood hinge bolts. Use a pair of needle nose pliers to squeeze the two tabs and push the clip through the hole to detach it from the hinge.



6. Once the brackets are installed, ditch lights can now be installed.

NOTE: Ditch lights are not included with this kit.

FINAL STEPS

Make sure all bolts and parts are tightened and secured in place. Conduct a final check for alignment of the hood and clearance around the brackets.

Periodically, recheck the alignment of the brackets and make sure there is proper clearance around and along the length of the bracket. Failure to follow proper maintenance procedures may cause damage and void your warranty.





Also available for Toyota 2010-2022 4Runner 4.0L V6



Contact an authorized HPS Performance dealer or visit us at <u>hpsperformanceproducts.com</u> for more details