

KEY TO COMPONENTS	TOOLS NEEDED
A. 1 ea. Grille	Ratchet
B. 1ea. Wiring harness	10mm socket
C. 8ea. Bolts	Plastic rivet removal tool or similar tool
D. 2ea. Mounting brackets	

A



B



C



D



ELECTRICAL INSTALLATION



This grill comes complete with light markers which need to be connected to a power source. Failure to properly make these connections could result in damage to the LED lights and/or your vehicle and may result in personal injury. If you are not qualified to make the proper connections, we highly recommend that you contact an installation expert to complete the connections.



Please take a few minutes to read and thoroughly familiarize yourself with the installation procedures outlined in this manual. Following the steps as outlined will save you time and help reduce mistakes. Once the instructions are reviewed, if you feel that you are not capable of safely installing the parts seek the help of a qualified installation expert to help you complete the job. The manufacture is in no way responsible for any personal injury or vehicle damage that may occur during the installation.

NOTES ON INSTALLATION

Please read and understand all instructions prior to beginning the installation process.

Pre-fit all panels as you proceed with the installation before attempting to bolt into position. This will enable you to understand exactly how the part is intended to fit onto vehicle.

Do NOT over-tighten screw.

If the instructions call for you to save and re-install parts set them aside in a protected area so as not to damage them.

FACTROY GRILLE REMOVAL



Step 1
Open vehicle's hood. Using a plastic removal tool or similar tool locate and remove 2 factory clips circled above holding the factory grille onto vehicle. Save hardware for reinstallation.



Step 2
Using a 10mm socket locate and remove 2 factory bolts securing the factory grille onto vehicle. Save hardware for reinstallation.



Step 3
Firmly grab and pull factory grille off of vehicle. Discard factory grille.

INSTALLING NEW GRILLE



Step 1
Place supplied grille (A) onto vehicle as shown above.



Step 2
Reinstall 2 factory clips circled above to secure grille in place.



Step 3
Using a 10mm socket reinstall 2 factory bolts to secure grille onto vehicle.

Proceed to make electrical connections for the LED lights. If you are not qualified to make the proper connections, we highly recommend that you contact an installation expert to complete the connections.



This completes the installation.