

PO Box 886 Office: (620) 325-9325

INSTALLATION INSTRUCTIONS **BIGBOY BRACKETS** Collinsville, OK 74021 1995-2001 CHEROKEE XJ MODEL JEEP

JBBXJ250 DRIVER/PASSENGER

- 1. Remove seat from the Jeep retaining the original bolts and flange nuts as you will use them to reattach seat frames to the floor of the Jeep. Be sure to disconnect the seat belt indicator wire from beneath the seat.
- 2. Place removed seat on it's back and remove (4) 13mm flange nuts (A) holding the factory slides to the seat and remove the slides.
- 3. Bolt on the BigBoy Brackets (E) using the (4) $\frac{5}{16}$ " x 1" carriage bolts (B) supplied. Use the flatwasher (C) and the nyloc nut(D) to secure the brackets to the factory slides. Make sure the extra 3" of the bracket is toward the front of the seat.
- 4. Before you can bolt the BigBoy Bracket and factory slide on the left floor bracket you must make two cuts in the left seat bracket and bend the tab up to the vertical side of the seat frame (see FIG. 2). You can now bolt the left BigBoy Bracket with the factory slide to the floor bracket. The right seat frame does not need modified




FIG. 1 DRIVER'S SIDE INSTALLATION

5. Now you can bolt the seat back into the Jeep and enjoy 3" additional leg room. Be sure to reconnect the seat belt indicator wire underneath the seat.

Liability Release

The purchaser of this product agrees that the manufacturer of this product has no responsibility or liability for errors in installation and/or resulting injury and/or accidents resulting from or associated with use and/or installation of this product.

Purchaser agrees to release manufacturer from any and all liability for personal injuries including death and property losses or damage occasioned by, or in connection with any activity or accommodations for use and/or installation of this product, either professionally installed or self installed.

Purchaser furthermore agrees to hold harmless and indemnify said manufacturer organization(s) its directors, employees and agents, for any liability sustained by use and/or modifications of product or vehicle. including claims for damages, losses, injuries, and expenses arising out of or resulting from use of product.




FIG. 2 SEAT FRAME MODIFICATION